



# GRADE NO. 2 DIESEL S-15

## #2 ULSD CLEAR ON-ROAD

GAS OILS

TEST DESCRIPTION	TEST METHOD	SPECIFICATIONS		TYPICAL
		Min	Max	
<b>Physical Properties</b>				
Gravity, API, 60°F	D-4052			33.0
Specific Gravity, 60/60°F	D-1250			0.8602
Pounds per Gallon	D-1250			7.162
Flash, PMCC, °C	D-93	52		67
Viscosity, 40 °C, cst	D-445	1.3		2.5
Sulfur, mg/kg	D-7039		15	5
Copper Strip Corrosion	D-130		3	1A
Carbon Residue, Ramsbottom, 10%	D-524		0.35	0.07
Pour Point, °C	D-97			-80
Cloud Point, °C	D-5773			-40
Water & Sediment	D-2709			<0.01
Cetane Number	D-613			42
Color, Saybolt	D-156			+28
Color	D-1500			L 0.5
<b>Hydrocarbon Type – FIA</b>	D-1319			
Aromatics			35	12
<b>Distillation, °F</b>	D-86			
90%		540	640	575

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

**Health And Safety Information** See separate Safety Data Sheets available on request.

Cross™ and Corsol™ are trademarks of Cross Oil Refining & Marketing, Inc., All other marks are property of their respective owners.

**Cross Oil Refining & Marketing, Inc.**

Smackover, AR 71762 | USA | Phone 800 864-6275 | [www.crossoil.com](http://www.crossoil.com)

Product Data Sheet Revision 01/2018